



NOTES:

1. BOLLARD TO BE CONSTRUCTED OF BLACK POWDER COATED STAINLESS STEEL. WIRING ACCESS OPENING TO BE PROVIDED IN LEAST VISIBLE SIDE OF BOLLARD.
2. WELDED BASE PLATE MAY BE FLUSH WITH FRONT OR BACK OF BOLLARD AS APPROPRIATE. BASE PLATE TO INCORPORATE $\frac{5}{8}$ " \varnothing DRILLED HOLES FOR ANCHORING TO CONCRETE WITH $\frac{1}{2}$ " \varnothing X 4" SS EXPANSION ANCHORS.
3. ALL EXPOSED WIRING LOCATED OUTDOORS TO BE INSTALLED IN $\frac{3}{4}$ " RIGID CONDUIT OR "SEALTITE".
4. OPTIONAL INSTALLATION: ACTIVATION COLUMN MAY BE INSTALLED ON MASONRY WALL INSTEAD OF BOLLARD, PROVIDED IT IS MOUNTED WITH NO EXPOSED RACEWAY AND LOCATED ALONG THE ACCESSIBLE ROUTE TO THE ENTRANCE.
5. ACTIVATION COLUMNS MOUNTED IN EXTERIOR BOLLARDS OR WALLS SHALL BE WEATHERTIGHT.

	0	4/9/10	ORIGINAL ISSUE
1	1/31/11	ADDENDUM 1	# DATE REVISION DESCRIPTION

AUTOMATIC DOOR OPENER CONTROL STATION

Date: June 15, 2013
 Dwg. No.: 08 42 29-01