

SECTION 09 72 00 - WALL COVERING

PART I - GENERAL

1.1 RELATED DRAWINGS

- A. *Section 01 78 23 – Operation and Maintenance Data*

1.2 SUBMITTALS

- A. The Owner shall approve all wall covering submittals.

1.3 EXTRA STOCK

- A. Contractors shall provide an extra 10 percent of wall covering used along with manufacturer pattern number, run number, and sequential roll numbers.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. All wall coverings shall be commercial grade. High traffic areas shall use a heavy weight wall covering of approximately 23 ounces per square yard. Low traffic areas such as offices and conference rooms shall use no less than a medium weight wall covering of approximately 16 ounces per square yard.
- B. All wall coverings will have a graffiti resistant coating.

PART 3 - EXECUTION

3.1 PREPARATION

- A. All walls that will receive wall covering shall be primed. New drywall shall first be primed with latex wall primer, followed by a coat of alkyd or oil primer with a flat or eggshell sheen. New plaster or previously painted walls shall be primed with alkyd or oil primer.
- B. Sizing shall be applied after walls have been primed according to manufacturer's recommendation.
- C. Walls previously covered shall have all paste residues removed prior to new application.
- D. All corners (interior and exterior) shall be wrapped four to six inches.

3.2 SEQUENCING

- A. Wall covering shall be applied prior to items such as chair rail, baseboard, and trim.

PART 4 - SUBMITTALS

4.1 SCHEDULES

- A. *[Note to AE: Ensure schedules are submitted which will enable the replication or reorder of any manufactured product per Section 01 01 78 23 – Operation and Maintenance Data]*

END OF SECTION 09 72 00

This section of the *U of I Facilities Standards* establishes minimum requirements only.
It should not be used as a complete specification.